



Infusion Pattern Specification

COMPOSITION		
Construction	ISO2424	Tufted 1/12th Loop Pile
Pile Fibre	ISO2076	100% Solution Dyed Nylon
Primary Backing	ISO2424	Non-woven Polyester
Secondary Backing	ISO2424	Bitumen with glass fibre 3kg/m ²
Pile Height	ISO1766	2.7 mm ± 0.5mm
Total Height	ISO1765	6.5 mm ± 0.5mm
Pile Weight	ISO1958	590 gr/m ² ± 5%
Total Weight	ISO8543	4500 gr/m ² ± 10%
Pile Density	ISO1763	202,000 tufts/m ² ± 5%
Tile Size	EN994	50 x 50 cm
Tiles per Box		20 tiles per box (5m ²)

CLASSIFICATION		
Flammability (Fire Spread EN13501)	ISO11925	Fs ≤ 150mm within 20 seconds
Flammability (Radiant Panel EN13501)	ISO9239	C _{ir} -S1
Flammability (Hot Metal Nut)	BS4790	Low radius effects of ignition
Wear Resistance (Castor Chair Test)	ISO4918	Pass ≥ 2.4 (A – Continuous Use)
Electrical Vertical Resistance	ISO10965	Pass ≤ 10 ⁹ Ω
Electrostatic Propensity (Stroll Test)	ISO6356	Pass <2.0kV
Slip Resistance	EN13893	DS
Dimensional Stability	EN986	Pass <0.2%
Acoustic Impact Noise Reduction	ISO10140-1	25dB
Sound Absorption	ISO354	500Hz-0.07as, 1000Hz-0.16as, 2000Hz-0.28as, 4000Hz-0.32as
Colour Fastness – Light (CIELAB)	ISO105	≥6
Colour Fastness – Rubbing (CIELAB)	ISO105	≥5
Colour Fastness – Water (CIELAB)	ISO105	≥5
Classification for Use	ISO10874	Class 33 Commercial Heavy
Luxury Class Rating	EN1307	LC1

ENVIRONMENTAL	WARRANTY
Formaldehyde Emission HCHO - E1	10 Year Wear Warranty

CERTIFICATION	INSTALLATION

© The Floor Hub. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available on request.
Image colours shown may vary. Please order a quarter tile or full tile for verification before ordering.

The Floor Hub, Unit E Ventura Business Park, Old Parkbury Lane, Colney Street, Radlett AL2 2DB
Tel: 01923 211151 Email: sales@thefloorhub.co.uk


www.thefloorhub.co.uk




Infusion



Infusion
Vibrant textured carpet tile




Infusion




Iced



Shanghai




Chai




Earl Grey



Oolong



Kashmiri



Rooibos



Jasmine



Hibiscus



Spice



Sage



Cinnamon



Peppermint



Breakfast




Assam



Dajeerling

Vibrant textured carpet tile




Chamomile




Lemon Balm



Marrakech



Ginger



Gunpowder



Rosehip



Passion Flower

Infusion Pattern Specification

COMPOSITION

Construction	ISO2424	Tufted 1/12th Loop Pile
Pile Fibre	ISO2076	100% Solution Dyed Nylon
Primary Backing	ISO2424	Non-woven Polyester
Secondary Backing	ISO2424	Bitumen with glass fibre 3kg/m ²
Pile Height	ISO1766	2.7 mm ± 0.5mm
Total Height	ISO1765	6.5 mm ± 0.5mm
Pile Weight	ISO1958	590 gr/m ² ± 5%
Total Weight	ISO8543	4500 gr/m ² ± 10%
Pile Density	ISO1763	202,000 tufts/m ² ± 5%
Tile Size	EN994	50 x 50 cm
Tiles per Box		20 tiles per box (5m ²)

CLASSIFICATION

Flammability (Fire Spread EN13501)	ISO11925	Fs □ 150mm within 20 seconds
Flammability (Radiant Panel EN13501)	ISO9239	C _{fl} -S1
Flammability (Hot Metal Nut)	BS4790	Low radius effects of ignition
Wear Resistance (Castor Chair Test)	ISO4918	Pass ≥ 2.4 (A – Continuous Use)
Electrical Vertical Resistance	ISO10965	Pass ≤ 10 ⁹ Ω
Electrostatic Propensity (Stroll Test)	ISO6356	Pass <2.0kV
Slip Resistance	EN13893	DS
Dimensional Stability	EN986	Pass <0.2%
Acoustic Impact Noise Reduction	ISO10140-1	25dB
Sound Absorption	ISO354	500Hz-0.07as, 1000Hz-0.16as, 2000Hz-0.28as, 4000Hz-0.32as
Colour Fastness – Light (CIELAB)	ISO105	≥6
Colour Fastness – Rubbing (CIELAB)	ISO105	≥5
Colour Fastness – Water (CIELAB)	ISO105	≥5
Classification for Use	ISO10874	Class 33 Commercial Heavy
Luxury Class Rating	EN1307	LC1


ENVIRONMENTAL

Formaldehyde Emission HCHO - E1

WARRANTY

10 Year Wear Warranty

CERTIFICATION



INSTALLATION

© The Floor Hub. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available on request.

The Floor Hub HQ, Unit E Ventura Business Park, Colney Street, AL2 2DB
Tel: 01923 211151 Email: hello@thefloorhub.co.uk

Infusion Loop Specification

COMPOSITION

Construction	ISO2424	Tufted 1/10th Loop Pile
Pile Fibre	ISO2076	100% Solution Dyed Nylon
Primary Backing	ISO2424	Non-woven Polyester
Secondary Backing	ISO2424	Bitumen with glass fibre 3kg/m ²
Pile Height	ISO1766	2.9 mm ± 0.5mm
Total Height	ISO1765	6.2 mm ± 0.5mm
Pile Weight	ISO1958	540 gr/m ² ± 5%
Total Weight	ISO8543	4300 gr/m ² ± 10%
Pile Density	ISO1763	180,000 tufts/m ² ± 5%
Tile Size	EN994	50 x 50 cm
Tiles per Box		20 tiles per box (5m ²)

CLASSIFICATION

Flammability (Fire Spread EN13501)	ISO11925	Fs □ 150mm within 20 seconds
Flammability (Radiant Panel EN13501)	ISO9239	C _{fl} -S1
Flammability (Hot Metal Nut)	BS4790	Low radius effects of ignition
Wear Resistance (Castor Chair Test)	ISO4918	Pass ≥ 2.4 (A – Continuous Use)
Electrical Vertical Resistance	ISO10965	Pass ≤ 10 ⁹ Ω
Electrostatic Propensity (Stroll Test)	ISO6356	Pass <2.0kV
Slip Resistance	EN13893	DS
Dimensional Stability	EN986	Pass <0.2%
Acoustic Impact Noise Reduction	ISO10140-1	25dB
Sound Absorption	ISO354	500Hz-0.07as, 1000Hz-0.16as, 2000Hz-0.28as, 4000Hz-0.32as
Colour Fastness – Light (CIELAB)	ISO105	≥6
Colour Fastness – Rubbing (CIELAB)	ISO105	≥5
Colour Fastness – Water (CIELAB)	ISO105	≥5
Classification for Use	ISO10874	Class 33 Commercial Heavy
Luxury Class Rating	EN1307	LC1


ENVIRONMENTAL

Formaldehyde Emission HCHO - E1

WARRANTY

10 Year Wear Warranty

CERTIFICATION



INSTALLATION

© The Floor Hub. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available on request.

The Floor Hub HQ, Unit E Ventura Business Park, Colney Street, AL2 2DB

Tel: 01923 211151 Email: hello@thefloorhub.co.uk

www.thefloorhub.co.uk